

NOTES:

- 1. All dimensions are in millimetres unless otherwise stated.
- 2. * Where the depth of block exceeds 80mm then PC11 250 edgings should be used.

TYPICAL CROSS SECTION DETAIL OF BLOCK PAVING

100mm.) Blocks run parallel to kerbs.

PC slabs laid on mortar pads at a slope of 2:1

GRANITE SETTS TO ISLANDS, FOOTWAYS ETC

PC slabs laid on mortar pads at a slope of 2:1

PC laids laid on mortar pads at a slope of 2:1

PC edging

PC SLABS LAID ON EDGE

Class C15P concrete



©Crown copyright 2007. All rights reserved. Use of this Image is limited to viewing on-line and printing one copy. Lekestershire County Council. 100019271.

Leicestershire
County Council
DEPARTMENT OF HIGHWAYS

TRANSPORTATION AND

WASTE MANAGEMENT

TITLE:

STANDARD DRAWING

KERBS AND FOOTWAYS

GRANITE SETTS AND SLABS LAID ON EDGE

DRAWING NUMBER	DATE				
SD/11/4	MAY 2004				
AUTOCAD REF		SCALE			
K:\GENERAL\D9997STDDRG\SD114		NOT TO SCALE	Rev	Date	Notes on Revision